

5970

Application

(*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)
 (*)

• Drive alongside the cap and set the unit down.

Hawle-Power-Lift

- Remove the work unit and place over the cap.
- Line up the foot with the base of the cap.
- First attach the cap with the retaining block on the bolts.
- Tear out the bolts by pumping.
- Then extend the special mandrel through the hole and shake it lightly so that the rocker is sideways.
- Pump until the cover springs up.
- Cover plate to stop water from penetrating

	weight (kg)
5970000000	35.000

Characteristics

- Hydraulic cylinder and handpump, nominal load 20 tons
- For all street caps up to size 3
- Extension mandrel 17 mm 5979
- Extension mandrel 24 mm 5979
- Additional tools are possible on request

Material

• Chassis: INOX